

Wind Mitigation Inspection Certificate

03/07/2023 Inspection Date

Rookery Bay Maintenance inc Homeowner



1301 - 1315 Perico Point Circle (Garage M)
Street Address

Bradenton

City

34209

Zip Code

www.windmitigation.network 239 351 5513

Anyone utilizing this certificate, you understand and agree: Inspections we perform are visual documenting the information requested on the OIR-B1-1802 form. Wind Mitigation Network, Llc and our network of inspection companies make no warranty, expressed or implied, that new insurance premiums will be higher or lower. Any liability of our and our network of inspection company's performance is expressly limited to the inspection fee paid. If you have any questions please email: info@windmitigations.com.

Uniform Mitigation Verification Inspection Form

Maintain a copy of this form and any documentation provided with the insurance policy

Inspection Date: 03/07/2023							
Owner Information MASTER ASSOCIATION CERTIFICATE							
Owner	Name:Rookery Bay Mainter	nance inc		Contact Person:			
	s:1301 - 1315 Perico Point			Home Phone:			
City: B	radenton	Zip: 34209		Work Phone:			
County	[:] Manatee			Cell Phone: 941-376-	3177		
Insurar	ice Company:			Policy #:			
Year of	f Home: 1992	# of Stories: 1		Email: Nicole@sunsta	atemanagement.com		
accom	NOTE: Any documentation used in validating the compliance or existence of each construction or mitigation attribute must accompany this form. At least one photograph must accompany this form to validate each attribute marked in questions 3 though 7. The insurer may ask additional questions regarding the mitigated feature(s) verified on this form.						
the	Building Code: Was the structure built in compliance with the Florida Building Code (FBC 2001 or later) OR for homes located in the HVHZ (Miami-Dade or Broward counties), South Florida Building Code (SFBC-94)? ☐ A. Built in compliance with the FBC: Year Built For homes built in 2002/2003 provide a permit application with a date after 3/1/2002: Building Permit Application Date (MM/DD/YYYY)// ☐ B. For the HVHZ Only: Built in compliance with the SFBC-94: Year Built For homes built in 1994, 1995, and 1996 provide a permit application with a date after 9/1/1994: Building Permit Application Date (MM/DD/YYYY)// ☐ C. Unknown or does not meet the requirements of Answer "A" or "B"						
OR	of Covering: Select all roof covering: Year of Original Installation/Reering identified.		at no information was av				
	2.1 Roof Covering Type:	Permit Application Date	FBC or MDC Product Approval #	Year of Original Installation or Replacement	Provided for Compliance		
	☐ 1. Asphalt/Fiberglass Shingle	/					
	2. Concrete/Clay Tile	07/22/2022		2022			
	3. Metal	/					
	4. Built Up	/ /					
	5. Membrane						
	6. Other						
×							
	B. All roof coverings have a Miroofing permit application after						
	C. One or more roof coverings	*		3".			
	D. No roof coverings meet the	requirements of Answer "A	A" or "B".				
3. Roo	of Deck Attachment: What is th	e weakest form of roof de	ck attachment?				
	A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the fieldOR- Batten decking supporting wood shakes or wood shinglesOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift less than that required for Options B or C below.						
	B. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 12" inches in the fieldOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d nails spaced a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf.						
•	C. Plywood/OSB roof sheathin 24"inches o.c.) by 8d common decking with a minimum of 2 r. Any system of screws, nails, ac	nails spaced a maximum of ails per board (or 1 nail possibles), other deck fasten	of 6" inches in the field er board if each board is sing system or truss/raft	OR- Dimensional lumbs s equal to or less than 6 in er spacing that is shown to	er/Tongue & Groove ches in width)OR-o have an equivalent		
Inspec	Inspectors Initials AHP Property Address 1301 - 1315 Perico Point Circle (Bradenton 34209						

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure. OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155 Page 1 of 4

		or greater resistance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at least 182 psf.
		D. Reinforced Concrete Roof Deck.
		E. Other:
		F. Unknown or unidentified.
		G. No attic access.
4.		of to Wall Attachment: What is the <u>WEAKEST</u> roof to wall connection? (Do not include attachment of hip/valley jacks within eet of the inside or outside corner of the roof in determination of WEAKEST type)
		A. Toe Nails
		☐ Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or
		☐ Metal connectors that do not meet the minimal conditions or requirements of B, C, or D
	Mi	nimal conditions to qualify for categories B, C, or D. All visible metal connectors are:
		Secured to truss/rafter with a minimum of three (3) nails, and
		Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion.
	X	B. Clips
		Metal connectors that do not wrap over the top of the truss/rafter, or
		☐ Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails.
		C. Single Wraps Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side.
	П	D. Double Wraps
		Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or
		☐ Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side.
		E. Structural Anchor bolts structurally connected or reinforced concrete roof.F. Other:
		G. Unknown or unidentified
		H. No attic access
5.		of Geometry: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification).
	X	A. Hip Roof Hip roof with no other roof shapes greater than 10% of the total roof system perimeter.
		Total length of non-hip features: feet; Total roof system perimeter: feet B. Flat Roof Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of
		less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft C. Other Roof Any roof that does not qualify as either (A) or (B) above.
6.		 condary Water Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the
	<u></u>	sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss.
		B. No SWR.
		C. Unknown or undetermined.
ſn	spec	tors Initials AHP Property Address 1301 - 1315 Perico Point CircleBradenton 34209
		verification form is valid for un to five (5) years provided no material changes have been made to the structure or
••	nic	verturation form is valid for iin to tive (5) vears provided no material changes have been made to the structure or

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

7	Opening Protection: What is the weakest form of wind borne debris protection installed on the structure?

7. Opening Protection: What is the weakest form of wind borne debris protection installed on the structure? First, use the table to determine the weakest form of protection for each category of opening. Second, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings and (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable.

Opening Protection Level Chart		Glazed Openings				Non-Glazed Openings	
Place an "X" in each row to identify all forms of protection in use for each opening type. Check only one answer below (A thru X), based on the weakest form of protection (lowest row) for any of the Glazed openings and indicate the weakest form of protection (lowest row) for Non-Glazed openings.		Windows or Entry Doors	Garage Doors	Skylights	Glass Block	Entry Doors	Garage Doors
N/A	Not Applicable- there are no openings of this type on the structure	X	X	\times	X		
Α	Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights)					\times	
В	Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights)						
С	Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007						
D	Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance						
N	Opening Protection products that appear to be A or B but are not verified						
14	Other protective coverings that cannot be identified as A, B, or C						
Х	No Windborne Debris Protection						X

A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at
a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval
system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure
and Large Missile Impact" (Level A in the table above).

- Miami-Dade County PA 201, 202, and 203
- Florida Building Code Testing Application Standard (TAS) 201, 202, and 203

A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist

- American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996
- Southern Standards Technical Document (SSTD) 12
- For Skylights Only: ASTM E 1886 and ASTM E 1996
- For Garage Doors Only: ANSI/DASMA 115

	X in the table above		
	☐ A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above		
B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All Glopenings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection desin the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the follow for "Cyclic Pressure and Large Missile Impact" (Level B in the table above):			
	• ASTM E 1886 and ASTM E 1996 (Large Missile – 4.5 lb.)		
	• SSTD 12 (Large Missile – 4 lb. to 8 lb.)		
	• For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large Missile - 2 to 4.5 lb.)		
	\square B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist		
	☐ B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X		

A.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or

C. Exterior Opening Protection- Wood Structural Panels meeting FBC 2007 All Glazed openings are covered with plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above).

C.1 All Non-Glazed openings classified as A, B, or C in the table above, or no Non-Glazed openings exist

 \square C.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in the table above

☐ C.3 One or More Non-Glazed openings is classified as Level N or X in the table above

B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above

Inspectors Initials AHP Property Address 1301 - 1315 Perico Point Bradenton 34209

in the table above

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

☐ N. Exterior Opening Protection (unverified shutter s	vstems with no document	ation) All Glazed openings are protected with			
N. Exterior Opening Protection (unverified shutter systems with no documentation) All Glazed openings are protected with protective coverings not meeting the requirements of Answer "A", "B", or C" or systems that appear to meet Answer "A" or "B" with no documentation of compliance (Level N in the table above).					
☐ N.1 All Non-Glazed openings classified as Level A, B, C, o	r N in the table above, or no N	on-Glazed openings exist			
 N.2 One or More Non-Glazed openings classified as Level table above 	D in the table above, and no N	on-Glazed openings classified as Level X in the			
☐ N.3 One or More Non-Glazed openings is classified as Leve	el X in the table above				
X. None or Some Glazed Openings One or more Glaze	ed openings classified and I	Level X in the table above.			
MITIGATION INSPECTIONS MUST B Section 627.711(2), Florida Statutes, provi					
Qualified Inspector Name: Alexander Hernandez Piedra	License Type: Home Inspection	License or Certificate #: HI15079			
Inspection Company: Wind Mitigation Network LLC	,	Phone: 239-351-5531			
-	· (ahaalz ana)	203-001-0001			
 Qualified Inspector – I hold an active license as a X Home inspector licensed under Section 468.8314, Florida Statute training approved by the Construction Industry Licensing Board □ Building code inspector certified under Section 468.607, Florida 	es who has completed the statu and completion of a proficience				
☐ General, building or residential contractor licensed under Section					
☐ Professional engineer licensed under Section 471.015, Florida St	•				
☐ Professional architect licensed under Section 481.213, Florida St					
Any other individual or entity recognized by the insurer as posse verification form pursuant to Section 627.711(2), Florida Statute		ons to properly complete a uniform mitigation			
Individuals other than licensed contractors licensed under	Section 489.111, Florida S	tatutes, or professional engineer licensed			
under Section 471.015, Florida Statues, must inspect the str Licensees under s.471.015 or s.489.111 may authorize a direction conduct a mitigation verification inspection.					
I, Alexander Hernandez Piedra am a qualified inspector a	nd I personally performe	d the inspection or (licensed			
(print name) contractors and professional engineers only) I had my emplo	oyee (<u>N/A</u>) perform the inspection			
and I agree to be responsible for his/her work.	(print name	of inspector)			
Qualified Inspector Signature:	Date:	03/07/2023			
An individual or entity who knowingly or through gross ne					
subject to investigation by the Florida Division of Insurance Fraud and may be subject to administrative action by the appropriate licensing agency or to criminal prosecution. (Section 627.711(4)-(7), Florida Statutes) The Qualified Inspector who certifies this form shall be directly liable for the misconduct of employees as if the authorized mitigation inspector personally					
performed the inspection.					
<u>Homeowner to complete</u> : I certify that the named Qualified residence identified on this form and that proof of identification					
Signature:I	Date:03/07/2023	3			
** Homeowner not available for sig	nature				
An individual or entity who knowingly provides or utters a false or fraudulent mitigation verification form with the intent to obtain or receive a discount on an insurance premium to which the individual or entity is not entitled commits a misdemeanor of the first degree. (Section 627.711(7), Florida Statutes)					
The definitions on this form are for inspection purposes only and cannot be used to certify any product or construction feature as offering protection from hurricanes.					
Inspectors Initials <u>AHP</u> Property Address 1301 - 1315 I	Perico PoinBradenton	34209			
*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.					
OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155		Page 4 of 4			







Subject Property Elevation Elevation







Elevation Elevation Elevation







Elevation Elevation Elevation



-C



8D Nails Observed

8D Nails Observed

< 6" Nail Spacing







15/32" Roof Decking

SWR Verified

Clip RTW Connection







Unprotected Opening

Impact Rated Door(s)

Rooftop elevation