

Wind Mitigation Inspection Certificate

03/07/2023 Inspection Date

Rookery Bay Maintenance inc Homeowner



1335 - 1349 Perico Point Circle (Building O) Street Address

Bradenton

City

34209

Zip Code

www.windmitigation.network 239 351 5513

Anyone utilizing this certificate, you understand and agree: Inspections we perform are visual documenting the information requested on the OIR-B1-1802 form. Wind Mitigation Network, Llc and our network of inspection companies make no warranty, expressed or implied, that new insurance premiums will be higher or lower. Any liability of our and our network of inspection company's performance is expressly limited to the inspection fee paid. If you have any questions please email: info@windmitigations.com.

	ı	
	۰	

Uniform Mitigation Verification Inspection Form

Maintain a copy of this form and any documentation provided with the insurance policy

Inspection Date: 03/07/2023							
Owner Information MASTER ASSOCIATION CERTIFICATE							
Owner Name:Rookery Bay Maintenance inc				Contact Person:			
	s:1335 - 1349 Perico Point			Home Phone:			
City: B	radenton	Zip: 34209		Work Phone:			
County	[:] Manatee			Cell Phone:			
	ce Company:	<u> </u>		Policy #:			
Year of	Home: 1992	# of Stories: 2		Email: Nicole@sunsta	atemanagement.com		
NOTE: Any documentation used in validating the compliance or existence of each construction or mitigation attribute must accompany this form. At least one photograph must accompany this form to validate each attribute marked in questions 3 though 7. The insurer may ask additional questions regarding the mitigated feature(s) verified on this form.							
the	 1. <u>Building Code</u>: Was the structure built in compliance with the Florida Building Code (FBC 2001 or later) OR for homes located in the HVHZ (Miami-Dade or Broward counties), South Florida Building Code (SFBC-94)? A. Built in compliance with the FBC: Year Built For homes built in 2002/2003 provide a permit application with a date after 3/1/2002: Building Permit Application Date (MM/DD/YYYY)//						
OR	of Covering: Select all roof covering: Year of Original Installation/Reering identified.		at no information was av		ce for each roof		
	2.1 Roof Covering Type:	Permit Application Date	FBC or MDC Product Approval #	Year of Original Installation or Replacement	No Information Provided for Compliance		
	☐ 1. Asphalt/Fiberglass Shingle	/					
	2. Concrete/Clay Tile	07/19/2022		2022			
	☐ 3. Metal						
	4. Built Up	/					
	5. Membrane						
	6. Other						
×							
	B. All roof coverings have a M roofing permit application after						
	C. One or more roof coverings	*		3".			
	D. No roof coverings meet the requirements of Answer "A" or "B".						
3. Roo	of Deck Attachment: What is the	e weakest form of roof de	ck attachment?				
	A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the fieldOR- Batten decking supporting wood shakes or wood shinglesOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift less than that required for Options B or C below.						
	B. Plywood/OSB roof sheathing with a minimum thickness of 7/16" inch attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by 8d common nails spaced a maximum of 12" inches in the fieldOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d nails spaced a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf.						
	C. Plywood/OSB roof sheathing with a minimum thickness of 7/16" inch attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by 8d common nails spaced a maximum of 6" inches in the fieldOR- Dimensional lumber/Tongue & Groove decking with a minimum of 2 nails per board (or 1 nail per board if each board is equal to or less than 6 inches in width)OR-Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent						
Inspec	tors Initials <u>AHP</u> Property Ac	ldress 1335 - 1349 Pe	erico Point Circle (Bradenton 3420	99		

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure. OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155 Page 1 of 4

		182 psf.	esistance than 8d common hans spaced a maximum of 6 menes in the field of has a mean upfit resistance of at least				
		☐ D. Reinforced Concrete Roof Deck.					
		E. Other:					
		_	vn or unidentified.				
		G. No attic	c access.				
4.			Attachment: What is the <u>WEAKEST</u> roof to wall connection? (Do not include attachment of hip/valley jacks within ide or outside corner of the roof in determination of WEAKEST type)				
		A. Toe Na	ils				
			Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or				
			Metal connectors that do not meet the minimal conditions or requirements of B, C, or D				
	Mi	nimal condi	tions to qualify for categories B, C, or D. All visible metal connectors are:				
		>	Secured to truss/rafter with a minimum of three (3) nails, and				
		Ś	Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion.				
		B. Clips					
			1 '				
	\smile		position requirements of C or D, but is secured with a minimum of 3 nails.				
	X	C. Single V					
			Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side.				
		D. Double	•				
			Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or				
			Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side.				
		E. Structur F. Other:	Anchor bolts structurally connected or reinforced concrete roof.				
	П		vn or unidentified				
	П	H. No attic					
5.			w: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of re over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification).				
	×	A. Hip Ro	Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: feet; Total roof system perimeter: feet				
		B. Flat Ro					
		C. Other R					
6.	Sec	A. SWR (a sheathin dwellin B. No SW	ter Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the ng or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the g from water intrusion in the event of roof covering loss. R. vn or undetermined.				
ſn	spec	ctors Initials	AHP Property Address 1335 - 1349 Perico Point CircleBradenton 34209				
*]	This	verification	form is valid for up to five (5) years provided no material changes have been made to the structure or				

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

7.	Opening Protection: What is the weakest form of wind borne debris protection installed on the structure? First , use the ta
	determine the weakest form of protection for each cotagory of opening Second (a) check one answer below (A. R. C. N.

7. **Opening Protection:** What is the **weakest** form of wind borne debris protection installed on the structure? **First**, use the table to determine the weakest form of protection for each category of opening. **Second**, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings **and** (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable.

Opening Protection Level Chart		Glazed Openings				Non-Glazed Openings	
Place an "X" in each row to identify all forms of protection in use for each opening type. Check only one answer below (A thru X), based on the weakest form of protection (lowest row) for any of the Glazed openings and indicate the weakest form of protection (lowest row) for Non-Glazed openings.		Windows or Entry Doors	Garage Doors	Skylights	Glass Block	Entry Doors	Garage Doors
N/A	Not Applicable- there are no openings of this type on the structure		\times	\times	X	\times	\times
Α	Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights)						
В	Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights)						
С	Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007						
D	Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance						
N	Opening Protection products that appear to be A or B but are not verified						
	Other protective coverings that cannot be identified as A, B, or C						
Х	No Windborne Debris Protection	X					

- A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level A in the table above).
 - Miami-Dade County PA 201, 202, and 203
 - Florida Building Code Testing Application Standard (TAS) 201, 202, and 203
 - American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996
 - Southern Standards Technical Document (SSTD) 12
 - For Skylights Only: ASTM E 1886 and ASTM E 1996
 - For Garage Doors Only: ANSI/DASMA 115

☐ A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist
A.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or
X in the table above

- ☐ A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above
- B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All Glazed openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level B in the table above):
 - ASTM E 1886 <u>and</u> ASTM E 1996 (Large Missile 4.5 lb.)
 - SSTD 12 (Large Missile 4 lb. to 8 lb.)
 - For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large Missile 2 to 4.5 lb.)
 - ☐ B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist
 - ☐ B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above
 - B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above
- □ <u>C. Exterior Opening Protection- Wood Structural Panels meeting FBC 2007</u> All Glazed openings are covered with plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above).
 - C.1 All Non-Glazed openings classified as A, B, or C in the table above, or no Non-Glazed openings exist
 - C.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in the table above
 - C.3 One or More Non-Glazed openings is classified as Level N or X in the table above

Inspectors Initials AHP Property Address 1335 - 1349 Perico Point Bradenton 34209

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

☐ N. Exterior Opening Protection (unverified shutter s	ystems with no document:	ation) All Glazed openings are protected with			
protective coverings not meeting the requirements of Ar with no documentation of compliance (Level N in the ta		rstems that appear to meet Answer "A" or "B"			
☐ N.1 All Non-Glazed openings classified as Level A, B, C, o	r N in the table above, or no N	on-Glazed openings exist			
 N.2 One or More Non-Glazed openings classified as Level I table above 	D in the table above, and no N	on-Glazed openings classified as Level X in the			
☐ N.3 One or More Non-Glazed openings is classified as Leve	el X in the table above				
X. None or Some Glazed Openings One or more Glaze	ed openings classified and I	Level X in the table above.			
MITIGATION INSPECTIONS MUST B Section 627.711(2), Florida Statutes, provi	~				
Qualified Inspector Name: Alexander Hernandez Piedra	License Type: Home Inspection	License or Certificate #: HI15079			
Inspection Company:	Tromo mopodion	Phone:			
Wind Mitigation Network LLC	(1	239-351-5531			
Mome inspector I hold an active license as a: (check one) Home inspector licensed under Section 468.8314, Florida Statutes who has completed the statutory number of hours of hurricane mitigation training approved by the Construction Industry Licensing Board and completion of a proficiency exam. Building code inspector certified under Section 468.607, Florida Statutes. General, building or residential contractor licensed under Section 489.111, Florida Statutes. Professional engineer licensed under Section 471.015, Florida Statutes. Professional architect licensed under Section 481.213, Florida Statutes. Any other individual or entity recognized by the insurer as possessing the necessary qualifications to properly complete a uniform mitigation verification form pursuant to Section 627.711(2), Florida Statutes. Individuals other than licensed contractors licensed under Section 489.111, Florida Statutes, or professional engineer licensed under Section 471.015, Florida Statues, must inspect the structures personally and not through employees or other persons. Licensees under s.471.015 or s.489.111 may authorize a direct employee who possesses the requisite skill, knowledge, and experience to conduct a mitigation verification inspection. I, Alexander Hernandez Piedra am a qualified inspector and I personally performed the inspection or (licensed (print name) contractors and professional engineers only) I had my employee (N/A) perform the inspection and I agree to be responsible for his/her work.					
Qualified Inspector Signature:	Date:	03/07/2023			
An individual or entity who knowingly or through gross negligence provides a false or fraudulent mitigation verification form is subject to investigation by the Florida Division of Insurance Fraud and may be subject to administrative action by the appropriate licensing agency or to criminal prosecution. (Section 627.711(4)-(7), Florida Statutes) The Qualified Inspector who certifies this form shall be directly liable for the misconduct of employees as if the authorized mitigation inspector personally performed the inspection.					
Homeowner to complete: I certify that the named Qualified residence identified on this form and that proof of identification	n was provided to me or my	Authorized Representative.			
	Date: 03/07/2023	3			
** Homeowner not available for sig					
An individual or entity who knowingly provides or utters a false or fraudulent mitigation verification form with the intent to obtain or receive a discount on an insurance premium to which the individual or entity is not entitled commits a misdemeanor of the first degree. (Section 627.711(7), Florida Statutes)					
The definitions on this form are for inspection purposes only and cannot be used to certify any product or construction feature as offering protection from hurricanes.					
Inspectors Initials <u>AHP</u> Property Address 1335 - 1349 F	Perico PoinBradenton	34209			
*This verification form is valid for up to five (5) years provinaccuracies found on the form.	ided no material changes	have been made to the structure or			
OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155		Page 4 of 4			







Subject Property Elevation Elevation







Elevation Elevation Elevation








Elevation Elevation Elevation





8D Nails Observed

8D Nails Observed

< 6" Nail Spacing







15/32" Roof Decking

SWR Verified

Single Wrap RTW Connection



Single Wrap RTW Connection